

LGR



■ **Grilles LGR**

Rectangular with adjustable louvers.

- To cover rectangular intake or exhaust air openings especially for flat ducting.
- Centrally adjustable louvers allow the adjustment of air flow volume.
- Corrosion resistant design made of galvanised steel in a white epoxy finish.
- Includes mounting frame which allows universal installation. When installing in thin walled ducts it must be fixed with 4 screws.

QVK



■ **Grilles QVK**

Square, with adjustable louvers.

- To cover intake or exhaust air openings with a square cross section.
- Centrally adjustable louvers allow the adjustment of air flow volume.
- Corrosion resistant design made of galvanised steel in a white epoxy finish.
- Includes mounting frame. Thereby suitable for flush mounted wall installation and without frame suitable for fixing via screws.

G 200–500



■ **Grilles G fixed**

To cover vents on walls and ceilings.

- Made of high quality, UV-resistant and impact resistant polymer.
- Compact flat design. Simple fixing via mounting materials which are included.
- Some models obscure view into ducting when installed.

■ **Model range**

| Type | Ref. no. | Colour | Fits to fan size mm |
|-------|----------|------------|---------------------|
| G 200 | 0255 | white | 200 |
| G 250 | 0256 | white | 250/280 |
| G 315 | 0798 | white | 315 |
| G 355 | 0799 | white | 355 |
| G 400 | 0800 | white | 400 |
| G 500 | 0801 | light grey | 450/500 |

G 100, 160



■ **Grilles G fixed**

To cover and insert in circular vent openings.

- Made of high quality and impact resistant polymer. Corrosion resistant and therefore suitable for indoor and outdoor applications.
- Simple installation using rear connecting sockets with conical shape. Foam strip for air tight connection is included. Fixed installation is ensured via four corner holes. Egg grille inserts can easily be removed for cleaning even when fixed.


■ **Model range**

| Type | Ref. no. | Fits nominal duct openings in mm |
|-------------|----------|----------------------------------|
| LGR 250/150 | 0927 | 228 x 128 |
| LGR 450/150 | 0928 | 428 x 128 |
| LGR 350/230 | 0929 | 328 x 208 |
| LGR 450/230 | 0930 | 428 x 208 |

■ **Model range**

| Type | Ref. no. | Fits up to fan size nominal size mm |
|---------|----------|-------------------------------------|
| QVK 200 | 0791 | 200 |
| QVK 250 | 0792 | 250 |
| QVK 315 | 0793 | 315 |
| QVK 355 | 0794 | 355 |
| QVK 400 | 0795 | 400 |

G 200 and 250




Dim. in mm – see table


■ **Model range**

| Type | Ref. no. | Nom. size in mm | Colour | Qty |
|-----------|----------|-----------------|--------|-----|
| G 100 | 0796 | 90/100 | white | 1 |
| G 100 B | 0782 | 90/100 | brown | 1 |
| G 100 VE* | 0828 | 90/100 | white | 12 |
| G 160 | 0893 | 150/160 | white | 1 |

* low cost quantity pack




Dim. in mm – see table




Dim. in mm – see table

G 315 – 500



Dim. in mm – see table



Dim. in mm – see table

| Type | Free cross section cm² | Dim. in mm B b | Wgt. kg |
|-------------|------------------------|-------------------|---------|
| LGR 250/150 | 160 | 250 150 | 0,6 |
| LGR 450/150 | 320 | 450 150 | 1,0 |
| LGR 350/230 | 430 | 350 230 | 1,2 |
| LGR 450/230 | 575 | 450 230 | 1,5 |

| Type | Free cross section cm² | Dim. in mm B | Weight kg |
|---------|------------------------|-----------------|-----------|
| QVK 200 | 320 | □ 250 | 0,8 |
| QVK 250 | 490 | □ 300 | 1,0 |
| QVK 315 | 680 | □ 350 | 1,3 |
| QVK 355 | 920 | □ 400 | 1,8 |
| QVK 400 | 1190 | □ 450 | 3,2 |

| Type | Dim. in mm | | | | | Wgt. kg |
|-------|------------|-----|-----|----|-----|---------|
| | □ A | B | C | D | Ø | |
| G 200 | 287 | 210 | 210 | 39 | 5,2 | 0,7 |
| G 250 | 337 | 240 | 240 | 39 | 5,2 | 0,9 |
| G 315 | 340 | 300 | 300 | 22 | 5,2 | 0,4 |
| G 355 | 390 | 350 | 350 | 22 | 5,2 | 0,4 |
| G 400 | 440 | 400 | 400 | 22 | 5,2 | 0,6 |
| G 500 | 540 | 490 | 465 | 30 | 5,2 | 1,8 |

| Type | Dim. in mm | | | | | Wgt. kg |
|-------|------------|-----|----|----|-----|---------|
| | □ b | □ B | C | S | Ø D | |
| G 100 | 90 | 140 | 28 | 15 | 100 | 0,8 |
| G 160 | 130 | 190 | 40 | 24 | 150 | 0,3 |