



*Incorporating*



**Fire dampers**

**NCA Series 100**  
Fire dampers - CE marked

- CE marked curtain type fire damper
- Assessed against the requirements of BS EN 15650
- Four installation methods all with 120 minute 'E' ratings
- Galvanised steel construction as standard, stainless steel optional
- Vertical installations for masonry walls and drywall partitions
- Horizontal installation for concrete floor slabs
- Available to suit square, rectangular, circular and flat oval ducting
- Now available with fixing lugs



## Index

### Introduction

- 3 - CE marking
- 4 - Product overview and features
- 5 - Damper design

### Testing and certification

- 6 - CE qualifying certification and corrosion testing
- 7 - Case leakage testing

### CE marked installations

- 8 - Installation guide
- 9 - Installation FD-1V  
HEVAC frame for masonry walls  
Vertical installation with 120 minute 'E' rating
- 10 - Installation FD-2VP  
Plate frame for drywall partitions  
Vertical installation with 120 minute 'E' rating
- 11 - Installation FD-2VM  
Plate frame for masonry walls  
Vertical installation with 120 minute 'E' rating
- 12 - Installation FD-2HC  
Plate frame for concrete floors  
Horizontal installation with 120 minute 'E' rating
- 13 - Guide: Why is it so important to use certified fire dampers?

### Dimensions

- 14 - Dimensions with HEVAC frame
- 15 - Dimensions with plate frame

### Damper options

- 16 - Installation accessories, operation methods and maintenance assisting options
- 17 - Status indicators

### Further information

- 18 - Installation and maintenance  
Important note - Installation into chlorinated environments
- 19 - EC Declaration of Performance
- 20 - Finish details and ordering codes

## Quality assurance

HVC Supplies (Stourbridge) Ltd is an ISO 9001 certified company.



Assessed to ISO 9001  
Cert/Ref No. 1186